

Sensor Description

Working with the Farmdeck app, the fuel tank sensor measures fuel tank levels using magneto strictive technology commonly used by fuel depots, oil terminals, oil field refineries and petrochemical companies.



Features

- Measures product level
- Measures water level
- Measures five-point temperature

Applications

- Gasoline
- Diesel
- Biodiesel
- Crude oil
- Palm oil (CPO)
- Kerosene
- Ethanol gasoline
- Water
- Light oil
- Chemical
- Methanol gasoline



Fuel Tank Monitoring

Datasheet | Published 20.06.2022

Mechanical Features

| | |
|-----------------|--|
| Housing | IP67 enclosure with twist capsule housing and mounting bracket |
| Dimensions (mm) | 340 x 180 x 120 mm with bracket |
| Weight | 420 g with battery |
| Case Material | UV-stabilized ABS plastic , stainless steel |

Device Power Supply

| | |
|-----------------------|-----------------------------------|
| Battery | Solar panel with 1000 mAh battery |
| Expected battery life | Up to 5 years |

Operating Conditions

| | |
|-------------|------------------|
| Temperature | -40°C to +125 °C |
|-------------|------------------|

Radio/Wireless Connection

| | |
|-------------------------------|---|
| Wireless technology | LoRaWAN 1.0.3/1.1 |
| Supported LoRaWAN device type | Class A End-device |
| Supported LoRaWAN Regions | US902 - 928,AS923, AU915 - 928, KR920-923 |
| Configuration | OTAA, ABP, ADR |

Data Type

| | |
|------------------------|------------------------------|
| 0-6 Bar gauge pressure | (0-87 psi) |
| Readings | 10 minutes - 1 hour readings |
| Accuracy | +/-1% FS |

Optional Cellular Connection

| | |
|---------------------|--|
| Wireless Technology | LTE-M/NB/IoT |
| Supported LTE Bands | LTE-M (Cat-M1): B1, B2, B3, B4, B5, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B66 NB-IoT (Cat-NB1/NB2): B1, B2, B3, B4, B5, B8, B12, B13 |
| SIM card and format | Internal Nano 4FF SIM |